



## OPK-509 TIRE CHANGER

More information please login  
[www.oparck.com](http://www.oparck.com)  
[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

### PRODUCT DESCRIPTION

- Pneumatically operated tilting column
- Capable of handling stiff, wide and low-profile tire
- The clamping jaws and mounting, demounting head armad of high quality alloy steel, and scientific structural design protects steel rim from and damage during operation



# OPK-509


## TIRE CHANGER

### Technical parameters

Model	OPK-509
Power supply	110V/220V/380V 50/60HZ
Motor power	0.8KW/1.1KW
Operating pressure	0.8-1MPa
Outside clamping	11-21"/279-533mm(11-23" optional)
Inside clamping	13-24"/330-610mm(13-26" optional)
Max.wheel diameter	41"/1100mm
Max.wheel width	13"/330mm
Bead break force	2500Kgf
Operating pressure	8-10bar
Noise	<70db
Net/Cross weight	220/240kgs
Packing size	1000×800×950mm



### Detail



Aluminium Pedal assembly



Wear-resistant plate for turntable



High-power motor




Aluminium small cylinder


### Standard Accessories



Complete gear box



Big cylinder



Column small cylinder



Motor



Mounting head



Clamp



Pedal



Five way valve

# OPARCK

More information please login:  
[www.oparck.com](http://www.oparck.com) [www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO., LTD.

NO.186 Mashan Road, Paojiang Industrial Zone, Shaoxing, Zhejiang, China  
 TEL: 0086-0575-84623366 FAX: 0086-0575-84623331  
 E-mail: lichao@sxdinggao.com



[www.oparck.com](http://www.oparck.com)



[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)



## OPK-509A TIRE CHANGER

More information please login  
[www.oparck.com](http://www.oparck.com)  
[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

### PRODUCT DESCRIPTION

- Pneumatically operated tilting column
- Simultaneous pneumatic horizontal and vertical arm locking
- Capable of handling stiff, wide and low-profile tire
- The clamping jaws and mounting, demounting head are made of high quality alloy steel, and scientific structural design protects steel rim from and damage during operation



# OPK-509A

## TIRE CHANGER

### Technical parameters

Model	OPK-509A
Power supply	110V/220V/380V 50/60HZ
Motor power	0.8KW/1.1KW
Operating pressure	0.8-1MPa
Outside clamping	11-21"/279-533mm(11-23" optional)
Inside clamping	13-24"/330-610mm(13-26" optional)
Max.wheel diameter	41"/1100mm
Max.wheel width	13"/330mm
Bead break force	2500Kgf
Operating pressure	8-10bar
Noise	<70db
Net/Cross weight	280/310kgs
Packing size	1000×800×950mm 1280×380×320mm



### Detail



Alloy claw and Φ75 cylinder



Wear-resistant plate for turntable



High-power motor




Reinforced right side helparm


### Standard Accessories



Complete gear box



Big cylinder



Column small cylinder



Motor



Mounting head



Clamp



Pedal



Five way valve

# OPARCK

More information please login:  
[www.oparck.com](http://www.oparck.com) [www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO., LTD.

NO.186 Mashan Road, Paojiang Industrial Zone, Shaoxing, Zhejiang, China  
 TEL: 0086-0575-84623366 FAX: 0086-0575-84623331  
 E-mail: lichao@sxdinggao.com



[www.oparck.com](http://www.oparck.com)



[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)



## OPK-516A TIRE CHANGER

More information please login  
[www.oparck.com](http://www.oparck.com)  
[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

### PRODUCT DESCRIPTION

- Pneumatic controlled tyre pressing device can be freely lifted and located at any position
- Tyre pressing roller of right help arm always protects tyre and rim
- Multi-function help arm has central positioning function which can make wheel and turntable homocentric



# OPK-516A

## TIRE CHANGER

### Technical parameters

Model	OPK-516A
Power supply	110V/220V/380V 50/60HZ
Motor power	0.8KW/1.1KW
Operating pressure	0.8-1MPa
Outside clamping	11-21"/279-533mm
Inside clamping	13-24"/330-610mm
Max.wheel diameter	40"/1000mm
Max.wheel width	13"/330mm
Bead break force	2500Kgf
Operating pressure	8-10bar
Noise	<70db
Net/Cross weight	200/220kgs
Packing size	1000×800×950mm



### Detail



Alloy claw and Φ75 cylinder



Wear-resistant plate for turntable



High-power motor




Tire press helparm


### Standard Accessories



Complete gear box



Big cylinder



Column small cylinder



Motor



Mounting head



Clamp



Pedal



Five way valve

# OPARICK

More information please login:  
[www.oparick.com](http://www.oparick.com) [www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO., LTD.

NO.186 Mashan Road, Paojiang Industrial Zone, Shaoxing, Zhejiang, China  
 TEL: 0086-0575-84623366 FAX: 0086-0575-84623331  
 E-mail: lichao@dinggaomechanical.com



[www.oparick.com](http://www.oparick.com)



[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)



## OPK-516 TYRE CHANGER

More information please login  
[www.oparck.com](http://www.oparck.com)  
[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

### PRODUCT DESCRIPTION

- The enlarged 24inch turetable is suitable for mounting and demounting larger and wider tires
- The clamping jaws and mounting, demounting head armad of high quality alloy steel, and scientific structural design protects steel rim from and damage during operation



# OPK-516

## TIRE CHANGER

### Technical parameters

Model	OPK-516
Power supply	110V/220V/380V 50/60HZ
Motor power	0.8KW/1.1KW
Operating pressure	0.8-1MPa
Outside clamping	11-21"/279-533mm
Inside clamping	13-24"/330-610mm
Max.wheel diameter	40"/1100mm
Max.wheel width	13"/330mm
Bead break force	2500Kgf
Operating pressure	8-10bar
Noise	<70db
Net/Cross weight	180/200kgs
Packing size	1000×800×950mm



### Detail



Alloy claw and Φ75 cylinder



Wear-resistant plate for turntable



大直径铝活塞气缸  
Large Diameter big piston cylinder




High-power motor

### Standard Accessories



Complete gear box



Big cylinder



Column small cylinder



Motor



Mounting head



Clamp



Pedal



Five way valve

# OPARCK

More information please login:  
www.oparck.com www.sxdinggao.en.alibaba.com

SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO., LTD.

NO.186 Mashan Road, Paojiang Industrial Zone, Shaoxing, Zhejiang, China  
TEL: 0086-0575-84623366 FAX: 0086-0575-84623331  
E-mail: lichao@dinggaomechanical.com



www.oparck.com



www.sxdinggao.en.alibaba.com





## OPK-996 WHEEL BALANCER

More information please login  
[www.oparck.com](http://www.oparck.com)  
[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

### PRODUCT DESCRIPTION

- Self calibrating and self diagnosis programs
- Static and standard dynamic balancing and special rim balancing
- It is safe and reliable with wheel protection cover Unbalance value displayed accurately, and the position to add the balance weight is indicated definitely



# OPK-996

## WHEEL BALANCER

THE PROTECTIVE COVER IS OPTIONAL



### Technical parameters

Model	OPK-996
Power supply	110V/220V/380V 50/60HZ
Motor power	0.5KW
Rim diameter	12-24"
Rim width	1.5-20"/40-510mm
Max.wheel diameter	960mm
Max.wheel weight	70kg
Balancing precision	±1g
Cycle time	8s
Noise	<70db
Net/Cross weight	80/100kgs
Packing size	900×800×1150mm

### Standard Accessories



High precision lengthening shaft



Motor



Standard cones



Quick lock nut



Keyboard



Circuit board



Circuit board




Counter plier



Wheel width calliper

### Optional Accessories



Motorcycle adaptor of wheel balancer



Universal adaptor



Large centring cone



Delicate plastic hood

# OPARCK

SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO., LTD.

More information please login:  
www.oparck.com www.sxdinggao.en.alibaba.com

NO.186 Mashan Road, Paojiang Industrial Zone, Shaoxing, Zhejiang, China  
TEL: 0086-0575-84623366 FAX: 0086-0575-84623331  
E-mail: lichao@dinggaomechanical.com



www.oparck.com



www.sxdinggao.en.alibaba.com



## OPK-990 WHEEL BALANCER

More information please login  
[www.oparck.com](http://www.oparck.com)  
[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

### PRODUCT DESCRIPTION

- Self calibrating and self diagnosis programs
- Static and standard dynamic balancing and special rim balancing
- It is safe and reliable with wheel protection cover Unbalance value displayed accurately, and the position to add the balance weight is indicated definitely



# OPK-990

## WHEEL BALANCER



### Technical parameters

Model	OPK-990
Power supply	110V/220V/380V 50/60HZ
Motor power	0.5KW
Rim diameter	12-24"
Rim width	1.5-20"/40-510mm
Max.wheel diameter	960mm
Max.wheel weight	70kg
Balancing precision	±1g
Cycle time	8s
Noise	<70db
Net/Cross weight	80/100kgs
Packing size	950×570×1100mm

### Standard Accessories



High precision lengthening shaft



Motor



Standard cones



Quick lock nut



Keyboard



Circuit board



Circuit board




Counter plier



Wheel width calliper

### Optional Accessories



Motorcycle adaptor of wheel balancer



Universal adaptor



Large centring cone



Delicate plastic hood

# OPARCK

More information please login:  
[www.oparck.com](http://www.oparck.com) [www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO., LTD.

NO.186 Mashan Road, Paojiang Industrial Zone, Shaoxing, Zhejiang, China  
 TEL: 0086-0575-84623366 FAX: 0086-0575-84623331  
 E-mail: lichao@dinggaomechanical.com



[www.oparck.com](http://www.oparck.com)



[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)