



## OPK-516A TIRE CHANGER

More information please login  
[www.oparck.com](http://www.oparck.com)  
[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

### PRODUCT DESCRIPTION

- Pneumatic controlled tyre pressing device can be freely lifted and located at any position
- Tyre pressing roller of right help arm always protects tyre and rim
- Multi-function help arm has central positioning function which can make wheel and turntable homocentric



# OPK-516A

## TIRE CHANGER

### Technical parameters

Model	OPK-516A
Power supply	110V/220V/380V 50/60HZ
Motor power	0.8KW/1.1KW
Operating pressure	0.8-1MPa
Outside clamping	11-21"/279-533mm
Inside clamping	13-24"/330-610mm
Max.wheel diameter	40"/1000mm
Max.wheel width	13"/330mm
Bead break force	2500Kgf
Operating pressure	8-10bar
Noise	<70db
Net/Cross weight	200/220kgs
Packing size	1000×800×950mm



### Detail



Alloy claw and Φ75 cylinder



Wear-resistant plate for turntable



High-power motor



Tire press helparm

### Standard Accessories



Complete gear box



Big cylinder



Column small cylinder



Motor



Mounting head



Clamp



Pedal



Five way valve

# OPARICK

More information please login:  
[www.oparick.com](http://www.oparick.com) [www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)

SHAOXINGDINGGAOMECHANICAL EQUIPMENT CO., LTD.

NO.186 Mashan Road, Paojiang Industrial Zone, Shaoxing, Zhejiang, China  
 TEL: 0086-0575-84623366 FAX: 0086-0575-84623331  
 E-mail: lichao@dinggaomechanical.com



[www.oparick.com](http://www.oparick.com)



[www.sxdinggao.en.alibaba.com](http://www.sxdinggao.en.alibaba.com)